

SabetoFLEX Primer

Primer for difficult and porous surfaces

DESCRIPTION

SabetoFLEX Primer is a primer based on polyisobutylene (PIB) and naphtha, hydrodesulfurized heavy. The product is developed for the pre-treatment of difficult or porous surfaces prior to the application of coatings or adhesive systems.

The product is manufactured from recycled offcuts from SabetoFLEX roofing membrane through a patented recycling system.

KEY BENEFITS

- Manufactured from recycled material
- Suitable for difficult and porous surfaces
- Good adhesion-promoting effect before further system build-up
- Practical 5 L packaging for construction site and workshop use



TECHNICAL INFORMATION

Product type	Primer / adhesion enhancer
Chemical base	Polyisobutylene (PIB) and naphtha, hydrodesulfurized heavy
Application	Pre-treatment of difficult or porous surfaces
Colour	Clear/yellowish with dark particles
Odour	Slight petroleum odour
Density	Approx. 0.8 g/cm ³
Flash point	> 61 °C
Viscosity	Medium-high (depends on PIB content)
Contents	5 litres
PR No.	2365178
CAS No.	64742-48-9
MAL code (1993)	3-1

DEVELOPED FOR

The product is used as a primer for the pre-treatment of difficult or porous surfaces prior to the application of coatings or adhesive systems.

DIRECTIONS FOR USE

Shake the container thoroughly before use. The substrate must be clean, dry and free from dust, oil, wax and loose particles. Apply the product evenly to the surface and allow it to act according to the specific build-up and work process. A suitability test should always be carried out on the actual substrate before full application.

STORAGE AND SHELF LIFE

Store tightly closed in the original packaging in a cool, dry and well-ventilated place. Protect from frost, direct sunlight and heat sources.

SAFETY AND HANDLING

Danger. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- If swallowed: Immediately call a Poison Centre/doctor. Do not induce vomiting.
- Wear safety glasses and nitrile gloves when handling.

LIMITATIONS

Technical data are based on available product data and information from the safety data sheet. The suitability of the product must always be assessed in relation to the specific construction, substrate and application.