

SabetoFLEX Activator

Activator for improved positioning and adhesion

DESCRIPTION

SabetoFLEX Activator makes the back side of SabetoFLEX products fluid.

Gives you the possibility to more easily adjust to vapor barrier membranes and corners into place.

When the back side of SabetoFLEX products becomes fluid, you can install on wood and other rough surfaces, where it penetrates into the surface and provides extremely good adhesion.

Displaces water. PFAS-free.



PRODUCT SPECIFICATIONS

Property	Value
Material	Heptane
Application	Rough surfaces such as wood and concrete, smooth surfaces such as plastic, fiberglass and thermo roofs
Color	Clear
Propellant	Butane/propane gas
Gross weight	500 g
Net content	375 ml
Packaging	12 pcs. per box. Also sold individually
Installation temperature	Max. 50 °C
Use temperature	Min. 0 to max. 50 °C
Safety	Keep away from heat, hot surfaces and open flames
Storage temperature	Do not store above 50 °C
Storage	Dry. Avoid direct sunlight
Fire	Flammable
Environmental impact	Harmful only through evaporation

DISCLAIMER

This technical data sheet is provided by SabetoFLEX ApS for information purposes only. The user is responsible for determining whether the product is suitable for the intended application and installation conditions.