

ElaProof ROOF Primer installation instructions

Applications

The ready-to-use ElaProof ROOF PRIMER is designed for use on a stone-surfaced felt roof before the ElaProof coating.

Chassis

Before applying ElaProof ROOF Primer, dirt, grease, dust and other loose material are removed from the substrate and the substrate is cleaned of old paint and surface layers.

Instructions

Before application, dirt, grease, dust and other loose material are removed from the substrate and the substrate is cleaned of old paint and surface layers.

Operating temperature:

(air and surface) over +5°C. The primer is applied in a thin, even layer so that all the substance is absorbed on the surface and no ponds are formed. Only one treatment is sufficient if the substrate is not very dry and absorbent.

Tools:

roller, brush or syringe. Tools are cleaned with water.

Shelf life:

12 months from manufacture, see jar. The product must be protected from frost and direct sunlight.

Drying time:

1-3 h depending on conditions and substrate.

Consumption:

The consumption varies depending on the roughness of the surface from 70 to 120 g/m²

Structural drawings



All structural drawings related to ElaProof products in DWG and PDF format from the [ProdLib-service](#)

Updated: 05/2023 | MA

All the information presented above is based on research results, our current knowledge and experience. They do not remove the responsibility of the user of the product to carry out his own tests and experiments, so that all factors and conditions that may affect the installation and use of the products should be considered. No guarantees regarding the properties or suitability of the product for specific purposes can be given based on this information. All descriptions, drawings, photos, information, proportions, portion sizes, weights, etc. are indicative. We are not responsible if the product is used contrary to the instructions presented here. It is the responsibility of the user of the product to test the suitability of the product for the purpose of use. We are only responsible for the quality of the product and guarantee that it will pass our critical quality control. Product information is updated regularly, however, it is the user's responsibility to obtain the latest valid product information, which can be found at www.elaproof.com. We reserve the right to make changes. © Build Care Oy